

**10-60KVA (3:3)
Built-in isolated
transformer**



Features

- High frequency on-line double conversion technology
- Advanced dual-core DSP control technology and 3-level technology
- Active power factor correction (APFC), input power factor up to 0.99
- System efficiency improved to 92%, energy saving rate is doubled
- Output power factor 1.0
- Dual input design, supporting independent bypass
- Advanced digital and parallel technology, providing higher reliability than single system
- Wide input voltage range
- 50 / 60 Hz auto-sensing frequency
- 50 / 60 Hz frequency conversion mode
- Working efficiency up to 95% in ECO mode
- Fan speed varies intelligently with load, reducing noise and extending its service life
- Conformal coating technology to make UPS operate in harsh environment for a long time
- Digitally controlled charger
- Ability to switch on the UPS by battery in the absence of mains power (Cold start)
- Zero switching time for UPS power supply mode when the mains power is unstable, ensuring the output is uninterrupted
- 5 inches LCD colorful touch screen, friendly human & machine interface
- Powerful background software for parameters configuration and online upgrade
- Linear derating in low voltage input, reducing battery discharging times, extending the service life of battery
- Intelligent battery management, automatic equalized and float charging control, charger dormancy control, improving the reliability of charger and extending the battery life
- Effective hardware and software protection, robust self-diagnosis function, abundant event log for future check
- Advanced multi-platform communication for UPS monitoring: Standard RS232, USB, RS485, dry contacts, Optional SNMP card and Wifi card
- Standard EPO & Parallel port

Applications

- IDC data exchange room
- ISP, Computer room
- Bank/ Bond Clearing Center
- Industrial Process Control Applications
- Precision instruments and equipment

Specifications

MODEL	HD9910T	HD9915T	HD9920T	HD9930T	HD9940T	HD9960T
Capacity	10kVA/ 10kW	15kVA/ 15kW	20kVA/ 20kW	30kVA/ 30kW	40kVA/ 40kW	60kVA/ 60kW
INPUT						
Rated voltage	380 / 400 / 415 Vac (L-L)					
Voltage range	304-478Vac (L-L) , full load 228V-304Vac (L-L), load decrease linearly according to the min phase voltage					
Rated frequency	50 / 60 Hz (auto-sensing)					
Frequency range	40 - 70 Hz					
Power factor	> 0.99					
Bypass voltage range	Selectable, default -20%- +15% Up limited : +10%, +15%, +20%, +25%; Down limited : -10%, -15%, -20%, -30%, -40%					
Bypass frequency range	Selectable, ±1Hz, ±3Hz, ±5Hz					
Input current THDi	<3% (full linear load)					
Bypass overload	<125%: long term operation; 125% ~130%: 10min; 130% ~ 150%: 1min; 150%~ 400%: 1s; >400%, less than 200ms					
OUTPUT						
Rated voltage	380 / 400 / 415 Vac (L-L)					
Voltage regulation	±3% (full linear load)					
Frequency	Synchronized with utility in mains mode, 50 / 60 Hz ±0.1% in battery mode					
Waveform	Pure sine wave					
Power factor	1					
Crest factor	3:1					
Output voltage THDv	<2% (full linear load), <5% (full non-linear load according to IEC / EN62040-3)					
Overload	<110%: 60min; 110% ~ 125%: 10min; 125% ~ 150%: 1min; >150%: 200ms					
BATTERIES						
Battery voltage	± 240 VDC (Selectable, 32 - 40pcs)					
Charger power	10A Max			15A Max		20A Max
Charger voltage precision	1%					
SYSTEM						
Efficiency	92% Max					
Transfer time	0 ms					
Max. number of parallel connections	2					
Protections	Short-circuit, overload, overtemperature, battery low voltage, overvoltage, undervoltage and fan failure					
Interface	Standard: RS232 , RS485 , USB , Battery cold start, Programmable dry contact. Option: SNMP card, Parallel kit					
Display	LED+ 5 inch LCD touch screen					
OTHERS						
Operation temperature	0°C - 40°C					
Storage temperature	-40°C ~ 70°C					
Relative humidity	0 - 95% Non condensing					
Altitude	<1000m, load derated 1% per 100m from 1000 - 2000m					
IP rating	IP 20					
Noise (1 meter)	58 dB			62 dB		
UPS dimension (WxDxH)(mm)	350 x 715 x 1032.5			350 x 845.2 x 132.5	350 x 809.5 x 1115.5	350 x 809.5 x 1185.5
Net weight (kg)	110	132	145	190	293	340

- All specifications are subject to change without notice
- Custom-made specifications are acceptable